

US006560582B1

(12) United States Patent Woodall

(10) Patent No.: US 6,560,582 B1

(45) **Date of Patent:** May 6, 2003

(54) DYNAMIC MEMORY PROCESSOR

(75) Inventor: Roger L. Woodall, Jewett City, CT

(US)

(73) Assignce: The United States of America as

represented by the Secretary of the

Navy, Washington, DC (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 09/477,653

(22) Filed: Jan. 5, 2000

(51) Int. Cl.⁷ G06F 15/18

(52) U.S. Cl. 706/15; 706/18; 706/20; 706/27

(56) References Cited

U.S. PATENT DOCUMENTS

5,440,662 A	* 8/1995	Sukkar 704/236
5,613,037 A		Sukkar 704/256
5,629,870 A	• 5/1997	Farag et al 700/286
5,666,467 A	• 9/1997	Colak 706/33
5,719,480 A		Bock et al 318/568.11
5,745,382 A	• 4/1998	Vilim et al 706/16
5,845,271 A	• 12/1998	Thaler 706/16
5,852,815 A	• 12/1998	Thaier 706/16
5,852,816 A	• 12/1998	Thaler 706/20
6,014,653 A	• 1/2000	Thaler 706/16
6,105,015 A	* 8/2000	Nguyen et al 706/26
6,192,360 B1	• 2/2001	Dumais et al 707/6
6,301,572 B1	• 10/2001	Harrison 706/52

OTHER PUBLICATIONS

Constrained Neural Network Based Identification of Harmonic Sources, R. K. Hartana, Member, IEEE & G.G. Richards, Member, IEEE, (1990).*

Harmonic Sources Monitoring and Identification Using Neural Networks, R. K. Hartana, Member, IEEE & G.G. Richards, Member, IEEE, (1990).*

Neural Network for Estimation of Harmonic Components in a Power System, S. Osowski, IEEE Proceeding, Mar. 1992.* Neural Network Approach of Harmonics Detection, A.A. Mohd Zin, Md. Rukonmuzzaman, H. Shaibon, K.L. Lo, IEEE Catalogue No: 98Ex137 (1998) IEEE.*

(List continued on next page.)

Primary Examiner—John Follansbee
Assistant Examiner—Michael B. Holmes
(74) Attorney, Agent, or Firm—James M. Kasischke;
Michael F. Oglo; Jean-Paul Nasser

(57) ABSTRACT

A dynamic memory processor for time variant pattern recognition and an input data dimensionality reduction is provided having a multi-layer harmonic neural network and a classifier network. The multi-layer harmonic neural network receives a fused feature vector of the pattern to be recognized from a neural sensor and generates output vectors which aid in discrimination between similar patterns. The fused feature vector and each output vector are separately provided to corresponding positional king of the mountain (PKOM) circuits within the classifier network. Each PKOM circuit generates a positional output vector with only one element having a value corresponding to one, the element corresponding to the element of its input vector having the highest contribution. The positional output vectors are mapped into a multidimensional memory space and read by a recognition vector array which generates a plurality of recognition vectors.

21 Claims, 12 Drawing Sheets

